



RED PRO X ORIGINAL

RESCUE AND EVACUATION DEVICE, BOX

- Extremely good lifting capacity
- Water sealed brake housing
- Intuitive and easy to use

The latest generation automatic evacuation and rescue device with superior properties.

SEGMENTS

- ✓ Pitch roof work
- ✓ General industry
- ✓ Tower climber
- ✓ MEWPs
- ✓ Offshore
- ✓ Confined space
- ✓ Wind energy

ARTICLES

087003223200	RESQ, RPX200 Original, 200m, box, vacuum, accs.
087003223175	RESQ, RPX200 Original, 175m, box, vacuum, accs.
087003212150	RESQ, RPX200 Original, 150m, box, vacuum, accs.
087003212125	RESQ, RPX200 Original, 125m, box, vacuum, accs.
087003212100	RESQ, RPX200 Original, 100m, box, vacuum, accs.
087003212075	RESQ, RPX200 Original, 75m, box, vacuum, accs.
087003212050	RESQ, RPX200 Original, 50m, box, vacuum, accs.
087003212083	RESQ, RPX200 Original, 83m, box, vacuum, accs.
087003212090	RESQ, RPX200 Original, 90m, box, vacuum, accs.
087003212105	RESQ, RPX200 Original, 105m, box, vacuum, accs.
087003212140	RESQ, RPX200 Original, 140m, box, vacuum, accs.
087003213160	RESQ, RPX200 Original, 160m, box, vacuum, accs.
087003223180	RESQ, RPX200 Original, 180m, box, vacuum, accs.

OVERVIEW

RESQ RPX is the latest generation of rescue and evacuation equipment from RESQ – designed and developed for easy use

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

with intuitive functions.

The RPX can handle most rescue scenarios in various industries and extreme environments, from evacuation from high heights, lifting from deep shafts to advanced rescues, the height worker can feel confident that the equipment performance is verified.

The design and functionality of the device are based on insights from professionals working at heights daily. RPX is designed to give height workers verified confidence in extreme environments and for easy implementation of user-training and inspections.

Single-sided use for safe handling - all features on frontside - no more losing valuable time, twisting and turning the device to double-check. Universal power tool-interface for heavy lifting, up to 255m. Top-mounted swivel for optimal positioning, even in tight conditions and confined space. Laser printed, easy to read data and pictograms, engraved direct and permanently on the body. 280 kg – 255m verified and tested decent weight and height!

The device comes with a lifting function where the connection of machine-driven accessories simplifies and facilitates lifting at longer distances as standard. With the help of a power tool, the equipment can lift a load of 140 kg at a distance of 255 meters.

RPX requires a minimum of training which equals Low TCO for maintenance of training certificates for your workforce. Due to the easily recognizable and intuitive design on both rescue equipment and accessories, the kit is both practical and cost-efficient to introduce to already trained workforce which holds GWO or similar height training certificate.

RPX Original is delivered as a complete set in RESQ Vacuum (service interval of 10 years), storage box in plastic and accessory kit.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

SPECIFICATION

PRODUCT PROPERTIES

Product includes	Rope, 2pc anchor sling 1,2m, 1pc anchor sling 0,8m, edge protector with steel carabiner twist lock, pulley 22kN, rescue rope grab, 2pc steel carabiner twist lock, bag, inspection set and box
Packaging type	Vacuum
Attaching connector 1	Device: Aluminum carabiner with swivel
Attaching connector 2	Rope: Aluminum carabiner
Gate strength (kN)	16.0
Gate feature	tri lock
Adjustable under load	Yes
Energy absorber	No
Fall indicator	No
Mechanics	Centrifugal brake
Lifting mechanics	Gear, ratio 1:9
Descent speed (m/s)	0,9-1,6
Maximum number of users	2
Maximum rope length (m)	255.0
Maximum descent	255 meters
Minimum load (kg)	40.0
Maximum load (kg)	200.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	50.0
Minimum breaking strength - MBS (kN)	20.0
Material	Polyamide, Aluminum , Techno polymers
Functions	Descend function, Lifting function
Extra functions	Lift with external power source
Rope	Polyamide/polyamide 32-braided kernmantel construction 9,6mm

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 1496 : 2017, EN 341 : 2011
Notified body	0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brøndby, Denmark
Other standards	ANSI Z359.4-2013, CSA Z259.2.3-12

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 + 10 years. Product lifecycle 10 years + 10 years after service
Warranty	2 year
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	Chinese (ZH), Czech (CS), Danish (DA), Dutch (NL), English (EN), Estonian (ET), Finnish (FI), French (FR), German (DE), Italian (IT), Norwegian (NO), Polish (PL), Portuguese (PT), Spanish (ES), Swedish (SV), Turkish (TR)

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE