



## ED PRO X BASIC

### EVACUATION DEVICE, BAG

- Intuitive and easy to use
- Ensures function at long and heavy descents
- Water sealed brake housing

The latest generation automatic device with superior properties.

#### SEGMENTS

- ✓ General industry
- ✓ Tower climber
- ✓ MEWPs
- ✓ Offshore
- ✓ Scaffolding
- ✓ Wind energy

## ARTICLES

087601111025	RESQ, EPX200 Basic, 25m, bag
087601111060	RESQ, EPX200 Basic, 60m, bag
087601111015	RESQ, EPX200 Basic, 15m, bag
087601111020	RESQ, EPX200 Basic, 20m, bag
087601111050	RESQ, EPX200 Basic, 50m, bag
087601111075	RESQ, EPX200 Basic, 75m, bag
087601111100	RESQ, EPX200 Basic, 100m, bag

## OVERVIEW

EPX is a intuitive and easy to use evacuation device for a applications within most areas. With a construction that ensures function at long and heavy descents and at the same time isolates heat from sensitive parts of the device.

EPX Minimal is delivered as a complete set with anchorage sling and bag for quick access to the equipment.

#### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. support@crestogroup.com  
www.crestogroup.com

**CRESTO GROUP**  
EXPECT MORE

## SPECIFICATION

### PRODUCT PROPERTIES

Product includes	Device, rope, 1,2m anchor sling and bag
Packaging type	Bag
Attaching connector 1	Device: Aluminum carabiner with swivel
Attaching connector 2	Rope: Aluminum carabiner
Gate strength (kN)	16.0
Gate feature	twist lock
Adjustable under load	Yes
Energy absorber	No
Fall indicator	No
Mechanics	Centrifugal brake
Descent speed (m/s)	0,9-1,6
Maximum number of users	2
Maximum rope length (m)	255.0
Maximum descent	255m
Minimum load (kg)	40.0
Maximum load (kg)	200.0
Minimum working temperature (c)	-30.0
Maximum working temperature (c)	50.0
Minimum breaking strength - MBS (kN)	20.0
Material	Polyamide, Aluminum , Techno polymers
Functions	Descend function
Rope	Polyamide/polyamide 32-braided kernmantel construction 9,6mm

### CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 341 : 2011
Notified body	0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brøndby, Denmark
Other standards	ANSI Z359.4-2013, CSA Z259.2.3-12

### ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
-------------------	----------------------

#### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. support@crestogroup.com  
www.crestogroup.com

**CRESTO GROUP**  
EXPECT MORE

Life span	10 years
Warranty	2 year
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), French (FR), Spanish (ES), Portuguese (PT), Italian (IT), Estonian (ET), Polish (PL), Chinese (ZH), Turkish (TR), Czech (CS), Dutch (NL)

## IMAGES

