



## DOUBLE PROGRESS CAPTURE PULLEY

### PULLEY

- Approved for work load of 800 kg
- Fits ropes with a diameter between 10 and 13 mm
- Breaking strength 40kN

Aluminum pulley with locking cam from ISC.

### SEGMENTS

- ✓ Rope access

## OVERVIEW

Double Capture Pulley from ISC is a perfect pulley with locking cam for building your own safe pulley system up to 5:1 advantage.

The locking function enables quick and easy securing of the load and the pulley is approved for a working load of 800 kg. Complete the equipment with a rope with a diameter between 10 and 13 mm.

## SPECIFICATION

### PRODUCT PROPERTIES

Adjustable under load	Yes
Energy absorber	No
Fall indicator	No
Mechanics	Bearing
Maximum number of users	2
Maximum load (kg)	800.0
Minimum breaking strength - MBS (kN)	40.0
Material	Aluminum
Functions	Descend function, Lifting function

### CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 12278 : 2007

### ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 years
Warranty	2 year
Identification	Serial number
RFID	No

### DOCUMENTS

Declaration of Conformity	No
Manual languages	German (DE), English (EN), Spanish (ES), French (FR), Italian (IT), Dutch (NL)

#### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. support@crestogroup.com  
www.crestogroup.com

**CRESTO GROUP**  
EXPECT MORE

## IMAGES



### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. [support@crestogroup.com](mailto:support@crestogroup.com)  
[www.crestogroup.com](http://www.crestogroup.com)

**CRESTO GROUP**  
EXPECT MORE