



SMARTLINE X EL/TELE EVACUATION EQUIPMENT

- Compact personal equipment
- Maximal user weight 140 kg
- Optimized for the Swedish pole rescue method

Our own personal evacuation equipment Smartline X is one of the worlds smallest evacuation device on the market with a remarkable capacity of 140 kg user weight. Smartline X El/Tele is developed for pole and tower workers.

SEGMENTS

- ✓ Telecom

ARTICLES

| | |
|-----------|--------------------------------|
| 012230140 | RESQ, Smartline X El/Tele, 15m |
| 012230141 | RESQ, Smartline X El/Tele, 25m |

OVERVIEW

Smartline X El/Tele is developed especially for pole and tower workers but can also be used for most evacuations and rescues for heights up to 25 meters. Smartline X, with its great capacity, although in small size and low weight, enables you always to carry it on your harness for your safety. Smartline X is a small, manually controlled descent device for evacuation. It can also shackle easily be configured for lifting a person shorter distances in a rescue.

The precision put into the details of this product is extraordinary. The line used in the device is made out of Aramide, which has fantastic durability. The cooling plates on the side make sure to keep the device and rope from overheating.

The Smartline X is certified to the PPE Regulation and in accordance with the EN 341 standard for one time use.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

SPECIFICATION

PRODUCT PROPERTIES

| | |
|---------------------------------|---|
| Product includes | One water sealed bag, one 1,6 m anchor sling, one rescue knife and one extra carabiner. |
| Packaging type | Bag |
| Attaching connector 1 | Device: Aluminum carabiner tri-lock |
| Attaching connector 2 | Rope/absorber: Aluminum carabiner tri-lock |
| Gate opening (mm) | 20.0 |
| Adjustable under load | Yes |
| Energy absorber | Yes |
| Fall indicator | No |
| Mechanics | Friction brake |
| Lifting mechanics | Method 1:3 |
| Descent speed (m/s) | 0,5-2 |
| Maximum number of users | 1 |
| Maximum rope length (m) | 200.0 |
| Maximum descent | 200 meter |
| Minimum load (kg) | 60.0 |
| Maximum load (kg) | 140.0 |
| Minimum working temperature (c) | -25.0 |
| Maximum working temperature (c) | 50.0 |
| Material | Nylon, Aluminum , Aramid |
| Functions | Descend function |
| Rope | Aramid 5,5mm, 16 twill braid coreless construction |

CLASSIFICATION

| | |
|---------------|---|
| PPE-category | Category 3 |
| EN-standard | EN 341 : 2011 |
| Notified body | 0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brøndby, Denmark |

ANNUAL INSPECTION

| | |
|-------------------|----------------------|
| Annual inspection | Yes, every 12 months |
| Life span | 7 years |
| Warranty | 2 year |

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

| | |
|----------------|---------------|
| Identification | Serial number |
| RFID | Yes |

DOCUMENTS

| | |
|---------------------------|---|
| Declaration of Conformity | Yes |
| Manual languages | English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), French (FR), Spanish (ES), Portuguese (PT), Italian (IT), Estonian (ET), Dutch (NL) |

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE