



SMARTLINE X EL/TELE VACUUM

EVACUATION EQUIPMENT

- Compact rescue equipment
- Always with you
- Optimized for the Swedish pole rescue method

Smartline X El/Tele Vacuum is developed for pole and tower workers and is one of the worlds smallest evacuation device on the market. This equipment comes packed in our signature vacuum solution. This evacuation equipment is customised for the Swedish Telecom and Energy industry.

SEGMENTS

✓ Telecom

ARTICLES

012230142	RESQ, Smartline X El/Tele Vacuum, 15m
012230143	RESQ, Smartline X El/Tele Vacuum, 25m

OVERVIEW

Smartline X El/Tele Vacuum is developed especially for pole and tower workers but can also be used for most evacuations and rescues for heights up to 25 meters. Smartline X, with its great capacity, although in small size and low weight, enables you always to carry it on your harness for your safety. Smartline X is a small, manually controlled descent device for evacuation. It can also easily be configured for lifting a person shorter distances in a rescue.

The precision put into the details of this product is extraordinary. The line used in the device is made out of Aramide, which has fantastic durability. The cooling plates on the side make sure to keep the device and rope from overheating. Packed and sealed in RESQ's proven vacuum prolongs the total lifetime of the product, ensures function and condition at the same time as the inspection cost are reduced.

The Smartline X is certified to the PPE Regulation and in accordance with the EN 341 standard for one time use.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.



SPECIFICATION

PRODUCT PROPERTIES


Product includes	One water sealed bag, one 1,6 m anchor sling, one rescue knife, one extra carabiner and one
Froduct includes	inspection set.
Packinging type	Vacuum
Attaching connector 1	Device: Aluminum carabiner tri-lock
Attaching connector 2	Rope/absorber: Aluminum carabiner tri-lock
Gate opening (mm)	20.0
Adjustable under load	Yes
Energy absorber	Yes
Fall indicator	No
Mechanics	Friction b rake
Lifting mechanics	Method 1:3
Descent speed (m/s)	0,5-2
Maximum number of users	1
Maximum rope length (m)	200.0
Maximum descent	200 meter
Minimum load (kg)	60.0
Maximum load (kg)	140.0
Minimum working temperature (c)	-25.0
Maximum working temperature (c)	50.0
Material	Nylon, Aluminum , Aramid
Functions	Descend function
Rope	Aramid 5,5mm, 16 twill braid coreless construction

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 341 : 2011
Notified body	0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brondby, Denmark

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 years
Warranty	2 year






PRODUCT SHEET

Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), French (FR), Spanish (ES), Portuguese (PT), Italian (IT), Estonian (ET), Dutch (NL)







IMAGES





