



# **ST 102 Q**

# **HARNESS ST 102 Q**

- Max 140 kg user weight
- Two sizes and quick buckles
- Textile loops for front attachment

Basic full-body harness with a rear steel D-ring and front webbing loops and quick connect buckles.

#### **SEGMENTS**


- ✓ Pitch roof work
- ✓ General industry

# **ARTICLES**

HS102QYB-A	SAFE TIME, ST 102 Q. WL ¤
HS102QYB-B	SAFE TIME, ST 102 Q, L/XL ¤

### **OVERVIEW**

ST 102 Q has adjustable buckles on the legs and chest and adjustable shoulder, chest and thigh straps. The harness is perfect for those that need a harness for more basic heigh work where work positioning isn't necessary. The harness is offered in two different sizes, M/L and L/XL.







# **SPECIFICATION**

#### **PRODUCT PROPERTIES**

Front A-point	Textile loops
Chest buckles	PVC buckle
Back A-point	Galvanized steel 50 mm> 22kN
Leg buckles	Quick buckles
Adjustable under load	No
Fall indicator	No
Maximum number of users	1
Maximum load (kg)	140.0
Minimum working temperature (c)	-20.0
Maximum working temperature (c)	60.0
Minimum breaking strength - MBS (kN)	15.0
Material	Polyamide

### **CLASSIFICATION**

PPE-category	Category 3
EN-standard	EN 361 : 2004
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic

# **ANNUAL INSPECTION**

Annual inspection	Yes, every 12 months
Life span	10 years
Warranty	2 year
Identification	Serial number
RFID	No

### **DOCUMENTS**

Declaration of Conformity	Yes
Manual languages	Czech (CS), Danish (DA), Dutch (NL), English (EN), Estonian (ET), Finnish (FI), French (FR), German (DE), Norwegian (NO), Polish (PL), Slovak (SK), Spanish (ES), Swedish (SV)



# **IMAGES**





