



FUSION PRO TWIN-FLEX FALL ARREST LANYARD 1602

- CE and ANSI certified
- Approved for 140 kg
- Elastic webbing

The Fusion Twin-Flex H-A is a double fall arrest lanyard with flexible webbing and ANSI certified "12ft", which can handle a user weight of up to 140 kg.

SEGMENTS

- ✓ General industry
- ✓ Tower climber
- ✓ Offshore
- ✓ Wind energy

ARTICLES

012203835	Fusion Pro Twin-Flex, 1,8m
-----------	----------------------------

OVERVIEW

A double fall arrest lanyard is designed to suit you who need to move when you work at heights. With double hooks you always have a hook anchored when you move with the other hook. This is to provide the optimum security on, for example, scaffolding, mobile platforms or industries.

Fusion Twin-Flex is manufactured as a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length of 1.8 meters. At the beginning of the rope there is an external absorber mounted which is released in case of a fall. Unlike Energy Twin-Flex this fall arrest lanyard is ANSI certified and are approved for a user weight up to 140 kg. Between the absorber and the lanyard there is an aluminum ring to increase flexibility in use

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

SPECIFICATION

PRODUCT PROPERTIES

Attaching connector 1	ANSI and CE certified triple lock carabiner in aluminum
Attaching connector 2	Big ANSI and CE certified aluminum hook with 64 mm opening
Gate strength (kN)	16.0
Energy absorber	Yes
Fall indicator	Yes
Mechanics	Tear-webbing absorber
Maximum number of users	1
Maximum load (kg)	140.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	100.0
Minimum breaking strength - MBS (kN)	25.0
Material	Polyamide, Polyester

CLASSIFICATION

EN-standard	EN 355 : 2002
Notified body	1019, WVUJ, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Other standards	ANSI Z359.13

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Warranty	2+1 year when registered in Inspector
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	Czech (CS), Danish (DA), Finnish (FI), French (FR), German (DE), Greek (EL), Norwegian (NO), Slovak (SK), Spanish (ES), Swedish (SV)

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE