



ST 103

HARNESS ST 103

- Max 140 kg user weight
- Light weight
- Belt with D-rings for positioning

Basic full-body harness with a rear steel D-ring and a front double textile loops. The harness is equipped with side D-rings which are used for work positioning.

SEGMENTS


- ✓ Pitch roof work
- ✓ General industry
- ✓ Tower climber
- ✓ MEWPs
- ✓ Scaffolding

ARTICLES

HS103SYB-A	SAFE TIME, ST 103, M/L ¤
HS103SYB-B	SAFE TIME, ST 103, L/XL ¤

OVERVIEW

ST 103 has a rear steel D-ring, front double textile loops and a reinforced belt with steel D-rings for work positioning. It has adjustable shoulder, chest and thigh straps. The harness is also equipped with loops on the belt for tools and carabiners as well as other equipment that weigh up to 10 kg. The harness is offered in two different sizes, M/L and L/XL.





SPECIFICATION

PRODUCT PROPERTIES

Front A-point	Textile loops
Chest buckles	PVC buckle
Back A-point	Galvanized steel 50 mm> 22kN
Side D-rings	D-rings of steel
Leg buckles	Manual steel buckles
Adjustable under load	No
Maximum number of users	1
Maximum load (kg)	140.0
Minimum working temperature (c)	-20.0
Maximum working temperature (c)	60.0
Minimum breaking strength - MBS (kN)	15.0
Material	Polyamide

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 358 : 2018, EN 361 : 2004
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 years
Warranty	2 year
Identification	Serial number
RFID	No

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	Czech (CS), Danish (DA), Dutch (NL), English (EN), Estonian (ET), Finnish (FI), French (FR), German (DE), Norwegian (NO), Polish (PL), Slovak (SK), Spanish (ES), Swedish (SV)



IMAGES



