



ST 109 Q COMFORT ROPE ACCESS HARNESS

HARNESS ST 109 Q COMFORT

- Max 140 kg user weight
- Light weight
- Quickbuckles

Comfortable 4 point harness, designed for technical work such as rope access.

SEGMENTS

- ✓ Tower climber
- ✓ Rope access

ARTICLES

| | |
|-------------|--------------------------------|
| HS109CCQB-A | |
| HS109CCQB-B | ST 109 Q Comfort Black L/XL |
| HS109CCQB-C | ST 109 Q COMFORT-C XXL (black) |
| HS109CQYB-A | |
| HS109CQYB-B | |
| HS109CQYB-C | |

OVERVIEW

Multi-purpose comfortable harness, designed for long-term work at height and rope access, with the possibility of securing the working position, with a rear steel eyelet, two front carrying eyes, side eyes on the belt which are intended for work positioning and their position can be adjusted according to the needs of the user. The safety harness ST 109Q Comfort-C is a version of the harness with quick-release buckles located on the thighs. M/L and L/XL.

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

SPECIFICATION

PRODUCT PROPERTIES

| | |
|--------------------------------------|-------------------------------|
| Front A-point | Aluminum 60 mm> 22kN |
| Chest buckles | Aluminium D- Ring 50 mm >22kN |
| Back A-point | Aluminium 60 mm> 22kN |
| Side D-rings | D-rings of aluminium |
| Side adjuster | Steel adjuster |
| Leg buckles | Quick buckles |
| Padding material | Mech padding |
| Adjustable under load | No |
| Maximum load (kg) | 140.0 |
| Minimum working temperature (c) | -20.0 |
| Maximum working temperature (c) | 60.0 |
| Minimum breaking strength - MBS (kN) | 15.0 |
| Material | Polyamide |

CLASSIFICATION

| | |
|---------------|--|
| PPE-category | Category 3 |
| EN-standard | EN 358 : 2018, EN 361 : 2004, EN 813 : 2008 |
| Notified body | 1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic |

ANNUAL INSPECTION

| | |
|-------------------|----------------------|
| Annual inspection | Yes, every 12 months |
| Life span | 10 years |
| Warranty | 2 year |
| Identification | Serial number |
| RFID | No |

DOCUMENTS

| | |
|---------------------------|--|
| Declaration of Conformity | Yes |
| Manual languages | Czech (CS), Danish (DA), Dutch (NL), English (EN), Estonian (ET), Finnish (FI), French (FR), German (DE), Norwegian (NO), Polish (PL), Slovak (SK), Spanish (ES), Swedish (SV) |

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE