



# CRESTO, SIMO PRO H-A

## WORK POSITIONING LANYARD

### 2353



- ANSI certified
- Strong against sharp edges
- Certified as anchorpoint

A work positioning lanyard with a simple one-hand adjustment and ANSI certified with ANSI carabiner and hook. End-loop for shortening the slack when climbing.

#### SEGMENTS

- ✓ General industry
- ✓ Tower climber
- ✓ Wind energy

## ARTICLES

|           |                           |
|-----------|---------------------------|
| 012204065 | Cresto, Simo Pro H-A 1,0m |
| 012204066 | Cresto, Simo Pro H-A 1,5m |
| 012204067 | Cresto, Simo Pro H-A 1,8m |
| 012204068 | Cresto, Simo Pro H-A 2,0m |
| 012204069 | Cresto, Simo Pro H-A 2,5m |

## OVERVIEW

Simo Pro H-A is a work positioning lanyard of a strong and soft polyamide rope of the highest quality. With its smooth rope grab you can easily adjust the tension in the rope with one hand. This lanyard is tested and approved for users up to 140 kg and is unique thanks to its certification for many environments. A unique feature is that the lanyard can be used as an anchor point for, for example, rescue equipment.

This model has ANSI certified carabiner and a big ANSI certified hook with 64 mm opening.

#### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. support@crestogroup.com  
www.crestogroup.com

**CRESTO GROUP**  
EXPECT MORE

## SPECIFICATION

### PRODUCT PROPERTIES

|                                      |   |
|--------------------------------------|---|
| Attaching connector 1                | ANSI certified trippellock carabiner in aluminum    |
| Attaching connector 2                | Big ANSI certified aluminum hook with 64 mm opening |
| Gate strength (kN)                   | 22.0  |
| Gate opening (mm)                    | 62.0  |
| Adjustable under load                | Yes   |
| Energy absorber                      | No  |
| Fall indicator                       | No  |
| Mechanics                            | Spring-loaded lever locking.                        |
| Maximum number of users              | 1   |
| Maximum load (kg)                    | 140.0   |
| Minimum working temperature (c)      | -40.0   |
| Maximum working temperature (c)      | 100.0   |
| Minimum breaking strength - MBS (kN) | 28.0  |
| Material                             | Polyamide   |
| Functions                            | Support function                                    |
| Rope                                 | 16 mm kern mantle rope in polyamide .               |

### CLASSIFICATION

|               |   |
|---------------|---|
| PPE-category  | Category 3  |
| EN-standard   | ANSI Z359.3:2017, EN 358 : 2018, EN 795 : 2012 Type B                       |
| Notified body | 1019, WVU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic |

### ANNUAL INSPECTION

|                   |  |
|-------------------|--|
| Annual inspection | Yes, every 12 months   |
| Life span         | 10 + 2 years. Product lifecycle 10 years + 2 years stock keeping |
| Warranty          | 2+1 year when registered in Inspector                            |
| Identification    | Serial number  |
| RFID              | Yes  |

### DOCUMENTS

|                           |     |
|---------------------------|-----|
| Declaration of Conformity | Yes |
|---------------------------|-----|

#### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. support@crestogroup.com  
www.crestogroup.com

**CRESTO GROUP**  
EXPECT MORE

|                  |   |
|------------------|---|
| Manual languages | Czech (CS), Danish (DA), Dutch (NL), English (EN), Estonian (ET), Finnish (FI), French (FR), German (DE), Greek (EL), Norwegian (NO), Slovak (SK), Spanish (ES), Swedish (SV) |
|------------------|---|

CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. support@crestogroup.com  
www.crestogroup.com

CRESTO GROUP  
EXPECT MORE

## IMAGES



### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. support@crestogroup.com  
www.crestogroup.com

**CRESTO GROUP**  
EXPECT MORE