



EVACUATION HARNESS

HARNESS 6711

- Easy to put on
- Lightweight
- Dual colour

Simple evacuation harness to be used with an evacuation device when the user doesn't have a fall protection harness.

SEGMENTS

- ✓ MEWPs
- ✓ Offshore
- ✓ Confined space
- ✓ Wind energy

ARTICLES

012232001	Evac. Harness 6711
-----------	--------------------

OVERVIEW

Evacuation harness in Crestos HI-Vis 44mm polyester webbing to be used with a rescue-/evacuation device. The two colored harness simplifies the dressing in stressful situation with only one adjustment and attachment point which save valuable time. The harness is available in one size to fit all users.

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

SPECIFICATION

PRODUCT PROPERTIES

Product includes	Evacuati harness
Front A-point	D-ring 45mm in galvanised steel
Adjustable under load	Yes
Maximum number of users	1
Maximum load (kg)	141.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	50.0
Material	Galvanized steel, Polyester

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 1498 : 2006
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Other standards	ANSI Z359.4-2013

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 years
Warranty	2 year
Identification	Serial number
RFID	No

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN), Slovak (SK)

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE