



# CRESTO, TWIN-EDGE FALL ARREST LANYARD 1504

- Double fall arrest lanyard
- No Hook or carabiner
- Edge tested 11,5 mm polyamide rope

A double fall arrest lanyard where the user moves alternately. Without hooks

#### **SEGMENTS**


- ✓ General industry
- ✓ Tower climber
- ✓ Scaffolding
- ✓ Wind energy

### **ARTICLES**

012203744	Cresto, Twin-Edge, 1,7m ( No Hooks )
-----------	--------------------------------------

# **OVERVIEW**

A fall arrest lanyard with rope that is tested and approved for users up to 100 kg. The 12 mm thick rope makes it enduring. The fall arrester is located in an openable bag to make it easier to carry out an annual inspection according to EN 365. The product is suitable for work where the user moves alternately and needs to reconnect. Tested and approved with fall over edge.







# **SPECIFICATION**

#### **PRODUCT PROPERTIES**

Attaching connector 1	No Carabiner
Attaching connector 2	No Hook
Adjustable under load	No
Energy absorber	Yes
Fall indicator	Yes
Mechanics	Tear-webbing absorber
Maximum number of users	1
Maximum load (kg)	100.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	100.0
Minimum breaking strength - MBS (kN)	15.0
Material	Polyamide
Rope	11,5 mm rope

# **CLASSIFICATION**

PPE-category	Category 3
EN-standard	EN 355 : 2002, PPE-R/11.074, V3
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic

# **ANNUAL INSPECTION**

Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Warranty	2+1 year when registered in Inspector
Identification	Serial number
RFID	Yes

# **DOCUMENTS**

Declaration of Conformity	Yes
Manual languages	Czech (CS), Danish (DA), Dutch (NL), English (EN), Estonian (ET), Finnish (FI), French (FR), German (DE), Greek (EL), Italian (IT), Norwegian (NO), Slovak (SK), Spanish (ES), Swedish (SV)





# **IMAGES**





