



# **WORKER ADJUSTABLE**

## **FALL ARREST LINE 1215**

- Durable 12 mm polyamide rope
- For users up to 140 kg
- Easily adjustable rope grab

A fall arrest line with an adjustable rope grab tested and approved for users up to 140 kg.

#### **SEGMENTS**


- ✓ Pitch roof work
- ✓ General industry
- ✓ Tower climber
- ✓ Confined space
- ✓ Scaffolding
- ✓ Telecom
- ✓ Wind energy

### **ARTICLES**

| 012202705 | Cresto, Worker Adjustable, 5 m  |
|-----------|---------------------------------|
| 012202710 | Cresto, Worker Adjustable, 10 m |
| 012202715 | Cresto, Worker Adjustable, 15 m |

#### **OVERVIEW**

This fall arrest line is made of a 12 mm thick rope of high quality, and the adjustable rope grab allows the product to be used easily in, for example, roof work. The fall arrest line is tested and approved for users up to 140 kg. The textile fall arrester is located in an openable bag to make it easier to carry out an annual inspection according to EN 365.





# **SPECIFICATION**

#### **PRODUCT PROPERTIES**

| Attaching connector 1                | Oval twist carabiner in aluminum, mounted with captive pin                |
|--------------------------------------|---|
| Attaching connector 2                | Oval twist carabiner in aluminum, mounted with captive pin                |
| Adjustable under load                | No  |
| Energy absorber                      | Yes   |
| Mechanics                            | Tear-webbing absorber on the rope grab                                    |
| Maximum number of users              | 1   |
| Maximum load (kg)                    | 140.0   |
| Minimum working temperature (c)      | -40.0   |
| Maximum working temperature (c)      | 100.0   |
| Minimum breaking strength - MBS (kN) | 15.0  |
| Material                             | Polyamide   |
| Rope                                 | 12 mm kern mantle rope in polyamide by the brand Patron from Teufelberger |

### **CLASSIFICATION**


| PPE-category  | Category 3   |
|---------------|--|
| EN-standard   | EN 353-2 : 2002  |
| Notified body | 1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic |


# **ANNUAL INSPECTION**

| Annual inspection | Yes, every 12 months                  |
|-------------------|---------------------------------------|
| Life span         | 10 years                              |
| Warranty          | 2+1 year when registered in Inspector |
| Identification    | Serial number                         |
| RFID              | Yes                                   |

### **DOCUMENTS**

| Declaration of Conformity | Yes   |
|---------------------------|---|
| Manual languages          | English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), French (FR), Spanish (ES) |





# **IMAGES**







