



SMARTLINE X ULTRA

EVACUATION EQUIPMENT

- Compact size
- Lightweight
- Big capacity

One of the worlds smallest evacuation device on the market with a remarkable capacity of 140 kg user weight and 200 meter descent distance.

SEGMENTS

- ✓ Tower climber
- ✓ MEWPs
- ✓ Offshore
- ✓ Wind energy

ARTICLES

012230120	RESQ, Smartline X Ultra, 50m
012230121	RESQ, Smartline X Ultra, 100m
012230122	RESQ, Smartline X Ultra, 125m
012230123	RESQ, Smartline X Ultra, 150m
012230124	RESQ, Smartline X Ultra, 200m
012230125	RESQ, Smartline X Ultra, 75m

OVERVIEW

RESQ Smartline X is in its class the smallest and lightest personal evacuation equipment to its high capacity and size. With a maximum load of 140 kg, maximum descent distance of 200 meters and a total weight of 3.8 kg (200 m), Smartline X becomes unique.

With weights from 2 to 3,8 kg, it's easy to carry the equipment attached to the harness to ensure availability in an emergency, wherever you are in the elevated workplace.

The Aramid rope has an incredible strength to diameter ratio and has heat resistance over 480 C. Smartline X can even be suitable where the sudden fire appears.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

SPECIFICATION

PRODUCT PROPERTIES

Product includes	Watertight bag, 1m anchor sling in Aramid
Packaging type	Bag
Attaching connector 1	Device: Aluminum carabiner tri-lock
Attaching connector 2	Rope/Absorber: Aluminum carabiner tri-lock
Gate opening (mm)	20.0
Adjustable under load	Yes
Energy absorber	Yes
Mechanics	Friction brake
Lifting mechanics	Method 1:3
Descent speed (m/s)	0,5-2m/s
Maximum number of users	1
Maximum rope length (m)	200.0
Maximum descent	200 meter
Minimum load (kg)	60.0
Maximum load (kg)	140.0
Minimum working temperature (c)	-25.0
Maximum working temperature (c)	50.0
Material	Nylon, Aluminum , Aramid
Functions	Descend function
Rope	Aramid 5,5 mm, 16 twill braid coreless construction

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 341 : 2011
Notified body	0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brøndby, Denmark

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	7 years
Warranty	2 year
Identification	Serial number

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

RFID	Yes
------	-----

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), French (FR), Spanish (ES), Portuguese (PT), Italian (IT), Estonian (ET), Dutch (NL)

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE