



LINK

CONNECTING LANYARD 9587

- 25 mm
- Durable polyamide webbing
- Sewn loops

Link is a connecting lanyard in polyamide webbing with sewn loops.

SEGMENTS

- ✓ General industry
- ✓ Offshore
- ✓ Rope access
- ✓ Telecom
- ✓ Wind energy

ARTICLES

012265170	Cresto, Link, 0,2 m
012265171	CRESTO, LINK, 0,3 M
012265172	Cresto, Link, 0,4 m
012265173	Cresto, Link, 0,5 m
012265177	CRESTO, LINK, 0,9 M
012265201	Cresto, Link, 4 m
012265202	Cresto, Link, 10 m

OVERVIEW

Link is a connecting line with a thickness of 25 mm and sewn loops. Its durable polyamide webbing make it robust and suitable work in several work areas.

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

SPECIFICATION

PRODUCT PROPERTIES

Energy absorber	No
Maximum number of users	1
Maximum load (kg)	140.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	100.0
Minimum breaking strength - MBS (kN)	22.0
Material	Polyamide
Rope	25 mm polyamide webbing

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 354 : 2010
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Warranty	2+1 year when registered in Inspector
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), French (FR), Spanish (ES)

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE