



ARMUR TWIN-H

SELF RETRACTABLE LANYARD W2TH

- Two lanyards and hooks
- Approved for horizontal use
- Light weight

The Armur Twin-H is a self retractable lanyard with double lanyards and hooks. It's approved for horizontal use which makes it suitable for scaffolding.

SEGMENTS

- ✓ General industry
- ✓ Scaffolding


ARTICLES

012212235 Cresto, Armur Twin-H, 2m	
------------------------------------	--

OVERVIEW

Armur Twin-H is, unlike Armur Single-H, a self retractable lanyard with two lanyards and hooks. With the help of a special adapter or carabiner, the lanyard are connected together creating a double self retractable lanyard with two connecting lanyards. This solution provides maximum security when the user needs to move between different points and at the same time be anchored all the time. Both self retractable lanyards work separately and adjust their position automatically with the help of a swivel and built-in mobility in the adapter. Unlike Tayl Twin-H, this modell is approved for horizontal use but has the same robust and attractive design.

With a self-retracting and self-locking connecting lanyard, braking mechanism reacts smoothly and limits the users fall distance to a minimum. A double self retractable lanyard is a smart alternative to a 2 meter double fall arrest lanyard as it creates more freedom of movement.







SPECIFICATION

PRODUCT PROPERTIES

Attaching connector 1	Oval screwgate carabiner in aluminum
Attaching connector 2	Aluminum hooks with 60 mm opening
Energy absorber	Yes
Fall indicator	Yes
Maximum number of users	1
Maximum load (kg)	140.0
Minimum working temperature (c)	-30.0
Maximum working temperature (c)	50.0
Minimum breaking strength - MBS (kN)	15.0
Material	Dyneema
Extra functions	User weight 140 Kg vertical / 100 Kg horisontal
Rope	20 mm Dyneema

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 360 : 2002, CNB/P11.060 Type A
Notified body	0598, SGS Fimko Ltd, Takomotie 8, FI-00380 Helsinki, Finland

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 years
Warranty	2+1 year when registered in Inspector
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), Estonian (ET)



IMAGES





