



N-267G-CP

CARABINER

- ANSI and EN approved
- Breaking strength 30kN
- Captive pin ready

N-267G-CP is a small steel carabiner with 2-way gate opening and captive pin.

SEGMENTS

- ✓ Pitch roof work
- ✓ General industry
- ✓ Tower climber
- ✓ MEWPs
- ✓ Offshore
- ✓ Confined space
- ✓ Scaffolding
- ✓ Rope access
- ✓ Telecom
- ✓ Wind energy

ARTICLES

012249949	Yoke, N-267G-CP
-----------	-----------------

OVERVIEW

N-267G-CP is a small carabiner with a 2-way gate opening, captive pin and a 17 mm opening. The carabiner is also both ANSI and EN approved.

SPECIFICATION

PRODUCT PROPERTIES

Gate strength (kN)	16.0
Gate opening (mm)	17.0
Gate feature	2-steps
Adjustable under load	No
Energy absorber	No
Fall indicator	No
Minimum breaking strength - MBS (kN)	30.0
Material	Steel
Extra functions	Captive pin

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 362 : 2004
Notified body	0321, SATRA Technology Centre, Wyndham Way, Telford Way, NN16 8SD Kettering, Northamptonshire, United Kingdom
Other standards	ANSI Z359.1

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Warranty	2 year
Identification	Batch number
RFID	No

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), Estonian (ET)

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE