



ALU-CTR-A D-SHAPE

CARABINER 9684

- ANSI and EN standard
- D-shaped
- Breaking strength 23 kN

Alu-CTR-A D-shape is an aluminum carabiner with 3-way locking.

SEGMENTS

- ✓ Pitch roof work
- ✓ General industry
- ✓ Tower climber
- ✓ MEWPs
- ✓ Scaffolding
- ✓ Telecom
- ✓ Wind energy

ARTICLES

012250122	Cresto, Alu-CTR-A D-shape
-----------	---------------------------

OVERVIEW

Alu-CTR-A D-shape is a carabiner that is both ANSI and EN certified. It is made of aluminum and has a breaking strength of 23 kN.

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

SPECIFICATION

PRODUCT PROPERTIES

Gate strength (kN)	16.0
Gate opening (mm)	20.0
Gate feature	3-way
Adjustable under load	No
Energy absorber	No
Fall indicator	No
Minimum breaking strength - MBS (kN)	23.0
Material	Aluminum

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 362 : 2004
Notified body	0321, SATRA Technology Centre, Wyndham Way, Telford Way, NN16 8SD Kettering, Northamptonshire, United Kingdom
Other standards	ANSI Z359.1

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Warranty	2 year
Identification	Serial number
RFID	No

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), Estonian (ET)

CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE