



## SMARTLINE X

### EVACUATION EQUIPMENT

- Compact personal equipment
- Maximal user weight 140 kg
- Can be mounted on the harness

Our own personal evacuation equipment Smartline X is one of the worlds smallest evacuation device on the market with a remarkable capacity of 140 kg user weight.

### SEGMENTS

- ✓ MEWPs
- ✓ Telecom

## ARTICLES

012230117	RESQ, Smartline X, 15m
012230118	RESQ, Smartline X, 25m

## OVERVIEW

Smartline X kit is developed especially for pole and tower workers but can also be used for most evacuations and rescues for heights up to 25 meters. Smartline X, with its great capacity, although in small size and low weight, enables you always to carry it on your harness for your safety. Smartline X is a small, manually controlled descent device for evacuation. It can also thanks to the special shackle easily be configured for lifting a person shorter distances in a rescue.

The precision put into the details of this product is extraordinary. The line used in the device is made out of Aramide, which has fantastic durability. The cooling plates on the side make sure to keep the device and rope from overheating.

The Smartline X is certified to the PPE Regulation and in accordance with the EN 341 standard for one time use.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. support@crestogroup.com  
www.crestogroup.com

**CRESTO GROUP**  
EXPECT MORE

## SPECIFICATION

### PRODUCT PROPERTIES

Product includes	A water sealed bag, an anchor sling 1,6m, a rescue knife
Packaging type	Bag
Attaching connector 1	Device: Aluminum carabiner tri-lock
Attaching connector 2	Rope/absorber: Aluminum carabiner tri-lock
Gate opening (mm)	20.0
Adjustable under load	Yes
Energy absorber	Yes
Fall indicator	No
Mechanics	Friction brake
Lifting mechanics	Method 1:3
Descent speed (m/s)	0,5-2
Maximum number of users	1
Maximum rope length (m)	200.0
Maximum descent	200 meter
Minimum load (kg)	60.0
Maximum load (kg)	140.0
Minimum working temperature (c)	-25.0
Maximum working temperature (c)	50.0
Material	Nylon, Aluminum , Aramid
Functions	Descend function
Rope	Aramid 5,5mm, 16 twill braid coreless construction

### CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 341 : 2011
Notified body	0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brøndby, Denmark

### ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	7 years
Warranty	2 year

#### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. support@crestogroup.com  
www.crestogroup.com

**CRESTO GROUP**  
EXPECT MORE

Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN), Swedish (SV), Norwegian (NO), Danish (DA), Finnish (FI), German (DE), French (FR), Spanish (ES), Portuguese (PT), Italian (IT), Estonian (ET), Dutch (NL)

## IMAGES



### CRESTO GROUP

Diabasgatan 16  
254 68 Helsingborg  
Sweden

T. +46 (0)42 563 00  
E. [support@crestogroup.com](mailto:support@crestogroup.com)  
[www.crestogroup.com](http://www.crestogroup.com)

**CRESTO GROUP**  
EXPECT MORE