Cresto, Fusion Pro Wind 1138

Harness 1138

- ANSI/EN certified
- Ergonomic
- Optimal fit

EN 358 : 2018 EN 361 : 2002



Product description

The Cresto Fusion Pro Wind 1138 is a high-performance full-body harness designed specifically for professionals working at height in the wind energy sector. Built for endurance, comfort, and rescue readiness, it combines advanced safety features with a fit that adapts to the demands of offshore and tower-based tasks. The harness is equipped with a helicopter-rescue-approved front D-ring and a rear D-ring with self-luminous functionality – providing enhanced visibility in low-light or confined environments. A unique teardrop-shaped webbing construction beneath the seat distributes pressure more evenly during suspension, reducing fatigue and improving ergonomics in case of a fall or extended hang time. Constructed using Cresto's signature NordGuard™ polyester webbing, the Fusion Pro Wind withstands extreme environmental temperatures from -40°C to +100°C. Coated steel D-rings and AustriAlpin quick-release buckles ensure top-tier corrosion resistance and ease of use, even with gloves or in wet conditions.

Product properties

Brand	Cresto
Adjustable under load	Yes
Back adjuster	Quick adjustable painted steel buckles
Back A-point	Plastic overmoeld steel ring self luminous PVC 53 mm
Minimum breaking strength - MBS (kN)	22
Chest buckles	Quick buckles in aluminum with stainless components Strength >22kN
Extra functions	The harness box includes Interchangeable parking loop for absorbing lanyard. Art nr 012290030.
Front A-point	Plastic overmoeld steel ring in self luminus PVC 53 mm
Leg buckles	Quick buckles in aluminum with stainless components Strength >22kN
Material	Polyester Nordguard ™
Maximum load (kg)	140

Min/Max load (kg)	30 / 140
Min/Max working temperature (c)	- 40 / 100
Maximum number of users	1
Maximum working temperature (c)	100
Minimum working temperature (c)	-40
Padding material	Breathable 3-D mesh
Side adjuster	Quick adjustable painted steel buckles
Side D-rings	Plastic overmoeld steel ring in black PVC 53 mm
PPE-category	Category 3
Declaration of Conformity	Yes
EN-standard	EN 358 : 2018, EN 361 : 2002
Warranty	2+1 year when registered in Inspector
Identification	Serial number
Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Other standards	ANSI Z359.11-2014
RFID	Yes

Article information

Article number	Article name	Size	Colors	Net weight (kg)
012200640	Cresto, Fusion Pro Wind, L/XL	L/XL	Black/Grey	2.77
012200630	Cresto, Fusion Pro Wind, S/M	S/M	Black/Grey	2.71
012200650	Cresto, Fusion Pro Wind, XXL	XXL	Black/Grey	2.87

Article number	Article name	GTIN	Tariff number	UNSPSC Code	Country of origin
012200640	Cresto, Fusion Pro Wind, L/XL	7350015799950	6307909899	46182306	Slovakia
012200630	Cresto, Fusion Pro Wind, S/M	7350015799943	6307909899	46182306	Slovakia
012200650	Cresto, Fusion Pro Wind, XXL	7350015790209	6307909899	46182306	Slovakia

Article number	Article name	Packaging type	W(cm)	H(cm)	L(cm)	Gross weight (kg)	Pieces / Pack
012200640	Cresto, Fusion Pro Wind, L/XL	Carton	22	22	38	3	
012200630	Cresto, Fusion Pro Wind, S/M	Carton	22	22	38	2.94	0
012200650	Cresto, Fusion Pro Wind, XXL	Carton	22	22	38	3.1	0