🛦 CRESTO SAFETY

RED PRO X Original

Rescue and evacuation device, box

- · Extremely good lifting capacity
- · Water sealed brake housing
- Intuitive and easy to use

EN 1496 : 2017 EN 341 : 2011



Product description

RESQ RPX is the latest generation of rescue and evacuation equipment from RESQ – designed and developed for easy use with intuitive functions. The RPX can handle most rescue scenarios in various industries and extreme environments, from evacuation from high heights, lifting from deep shafts to advanced rescues, the height worker can feel confident that the equipment performance is verified. The design and functionality of the device are based on insights from professionals working at heights daily. RPX is designed to give height workers verified confidence in extreme environments and for easy implementation of user-training and inspections. Single-sided use for safe handling - all features on frontside - no more losing valuable time, twisting and turning the device to doublecheck. Universal power tool-interface for heavy lifting, up to 255m. Top-mounted swivel for optimal positioning, even in tight conditions and confined space. Laser printed, easy to read data and pictograms, engraved direct and permanently on the body. 280 kg - 255m verified and tested decent weight and height! The device comes with a lifting function where the connection of machinedriven accessories simplifies and facilitates lifting at longer distances as standard. With the help of a power tool, the equipment can lift a load of 140 kg at a distance of 255 meters. RPX requires a minimum of training which equals Low TCO for maintenance of training certificates for your workforce. Due to the easily recognizable and intuitive design on both rescue equipment and accessories, the kit is both practical and cost-efficient to introduce to already trained workforce which holds GWO or similar height training certificate. RPX Original is delivered as a complete set in RESQ Vacuum (service interval of 10 years), storage box in plastic and accessory kit. Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

Product properties

Brand	RESQ					
Adjustable under load	Yes					
Attaching connector 1	Device: Aluminum carabiner with swivel					
Attaching connector 2	Rope: Aluminum carabiner					
Minimum breaking strength - MBS (kN)	20					
Descent speed (m/s)	0,9-1,6					

Energy absorber	No
Extra functions	Lift with external power source
Fall indicator	No
Functions	Descend function, Lifting function
Gate strength (kN)	16
Gate feature	tri lock
Lifting mechanics	Gear, ratio 1:9
Material	Polyamide, Aluminum , Techno polymers
Maximum descent	255m
Maximum load (kg)	200
Min/Max load (kg)	40/280
Min/Max working temperature (c)	-40/+60 °C
Maximum number of users	2
Maximum rope length (m)	255
Mechanics	Centrifugal brake
Mechanics Minimum load (kg)	Centrifugal brake 40
Minimum load (kg)	40
Minimum load (kg) Min/Max storage temperature (c)	40 -40/+60 °C
Minimum load (kg) Min/Max storage temperature (c) Packinging type	40 -40/+60 °C Vacuum
Minimum load (kg) Min/Max storage temperature (c) Packinging type Rope	40 -40/+60 °C Vacuum Polyamide/polyamide 32-braided kermantel construction 9,6mm
Minimum load (kg) Min/Max storage temperature (c) Packinging type Rope PPE-category	40 -40/+60 °C Vacuum Polyamide/polyamide 32-braided kermantel construction 9,6mm Category 3
Minimum load (kg) Min/Max storage temperature (c) Packinging type Rope PPE-category Declaration of Conformity	40 -40/+60 °C Vacuum Polyamide/polyamide 32-braided kermantel construction 9,6mm Category 3 Yes
Minimum load (kg) Min/Max storage temperature (c) Packinging type Rope PPE-category Declaration of Conformity EN-standard	40 -40/+60 °C Vacuum Polyamide/polyamide 32-braided kermantel construction 9,6mm Category 3 Yes EN 1496 : 2017, EN 341 : 2011
Minimum load (kg)Min/Max storage temperature (c)Packinging typeRopePPE-categoryDeclaration of ConformityEN-standardWarranty	40 -40/+60 °C Vacuum Polyamide/polyamide 32-braided kermantel construction 9,6mm Category 3 Yes EN 1496 : 2017, EN 341 : 2011 2 year
Minimum load (kg)Min/Max storage temperature (c)Packinging typeRopePPE-categoryDeclaration of ConformityEN-standardWarrantyIdentification	40 -40/+60 °C Vacuum Polyamide/polyamide 32-braided kermantel construction 9,6mm Category 3 Yes EN 1496 : 2017, EN 341 : 2011 2 year Serial number
Minimum load (kg)Min/Max storage temperature (c)Packinging typeRopePPE-categoryDeclaration of ConformityEN-standardWarrantyIdentificationAnnual inspection	40 -40/+60 °C Vacuum Polyamide/polyamide 32-braided kermantel construction 9,6mm Category 3 Yes EN 1496 : 2017, EN 341 : 2011 2 year Serial number Yes, every 12 months
Minimum load (kg)Min/Max storage temperature (c)Packinging typeRopePPE-categoryDeclaration of ConformityEN-standardWarrantyIdentificationAnnual inspectionLife span	40 -40/+60 °C Vacuum Polyamide/polyamide 32-braided kermantel construction 9,6mm Category 3 Yes EN 1496 : 2017, EN 341 : 2011 2 year Serial number Yes, every 12 months 10 + 10 years. Product lifecycle 10 years + 10 years after service

Article information

Article number	Article name	Colors	Net weight (kg)
087003223200	RESQ, RPX200 Original, 200m, box, vacuum, accs.	Black	25.73
087003223175	RESQ, RPX200 Original, 175m, box, vacuum, accs.	Black	24.2
087003212150	RESQ, RPX200 Original, 150m, box, vacuum, accs.	Black	20.31
087003212125	RESQ, RPX200 Original, 125m, box, vacuum, accs.	Black	18.72
087003212100	RESQ, RPX200 Original, 100m, box, vacuum, accs.	Black	17.2
087003212075	RESQ, RPX200 Original, 75m, box, vacuum, accs.	Black	15.67
087003212050	RESQ, RPX200 Original, 50m, box, vacuum, accs.	Black	14.15
087003212083	RESQ, RPX200 Original, 83m, box, vacuum, accs.	Black	16.16
087003212090	RESQ, RPX200 Original, 90m, box, vacuum, accs.	Black	16.59
087003212105	RESQ, RPX200 Original, 105m, box, vacuum, accs.	Black	17.5
087003212140	RESQ, RPX200 Original, 140m, box, vacuum ,accs.	Black	19.64
087003213160	RESQ, RPX200 Original, 160m, box, vacuum, accs.	Black	20.92
087003223180	RESQ, RPX200 Original, 180m, box, vacuum, accs.	Black	24.51

Article number	Article name	GTIN	Tariff number	UNSPSC Code	Country of origin
087003223200	RESQ, RPX200 Original, 200m, box, vacuum, accs.	7350015799219	84253900	46182312	Slovakia
087003223175	RESQ, RPX200 Original, 175m, box, vacuum, accs.	7350015799202	84253900	46182312	Slovakia
087003212150	RESQ, RPX200 Original, 150m, box, vacuum, accs.	7350015799196	84253900	46182312	Slovakia
087003212125	RESQ, RPX200 Original, 125m, box, vacuum, accs.	7350015799189	84253900	46182312	Slovakia
087003212100	RESQ, RPX200 Original, 100m, box, vacuum, accs.	7350015799172	84253900	46182312	Slovakia
087003212075	RESQ, RPX200 Original, 75m, box, vacuum, accs.	7350015799165	84253900	46182312	Slovakia
087003212050	RESQ, RPX200 Original, 50m, box, vacuum, accs.	7350015799158	84253900	46182312	Slovakia
087003212083	RESQ, RPX200 Original, 83m, box, vacuum, accs.	7350015799400	84253900	46182312	Slovakia
087003212090	RESQ, RPX200 Original, 90m, box, vacuum, accs.	7350015799417	84253900	46182312	Slovakia
087003212105	RESQ, RPX200 Original, 105m, box, vacuum, accs,	7350015799424	84253900	46182312	Slovakia

087003212140	RESQ, RPX200 Original, 140m, boy vacuum ,accs.	κ,	73500157994	431	842	53900	4618	82312	Slovakia	
087003213160	RESQ, RPX200 Original, 160m, box vacuum, accs.	κ,	73500157994	148	842	53900	4618	82312	Slovakia	
087003223180	RESQ, RPX200 Original, 180m, box vacuum, accs.	κ,	73500157994	455	842	53900	4618	82312	Sweden	
Article number	Article name	Pac	kaging type	W((cm)	H(cm)	L(cm)	Gross wei	ght (kg)	Pieces / Pack
087003223200	RESQ, RPX200 Original, 200m, box, vacuum, accs.	Box		0		0	0	0		
087003223175	RESQ, RPX200 Original, 175m, box, vacuum, accs.	Box		0		0	0	0		
087003212150	RESQ, RPX200 Original, 150m, box, vacuum, accs.	Box		0		0	0	0		1
087003212125	RESQ, RPX200 Original, 125m, box, vacuum, accs.	Box		0		0	0	0		
087003212100	RESQ, RPX200 Original, 100m, box, vacuum, accs.	Box		0		0	0	0		1
087003212075	RESQ, RPX200 Original, 75m, box, vacuum, accs.	Box		0		0	0	0		
087003212050	RESQ, RPX200 Original, 50m, box, vacuum, accs.	Box		0		0	0	0		1
087003212083	RESQ, RPX200 Original, 83m, box, vacuum, accs.	Box		0		0	0	0		
087003212090	RESQ, RPX200 Original, 90m, box, vacuum, accs.	Box		0		0	0	0		
087003212105	RESQ, RPX200 Original, 105m, box, vacuum, accs.	Box		0		0	0	0		
087003212140	RESQ, RPX200 Original, 140m, box, vacuum ,accs.	Box		0		0	0	0		
087003213160	RESQ, RPX200 Original, 160m, box, vacuum, accs.	Box		0		0	0	0		
087003223180	RESQ, RPX200 Original, 180m, box, vacuum, accs.	Box		0		0	0	0		