

Cresto, Core Single-Web 1505

Fall arrest lanyard 1505

- Single fall arrest lanyard
- No Hook or carabiner
- 20 mm webbing



EN 355 : 2002

Product description

A single fall arrest lanyard provides secure protection when working on skylifts and scaffolding. Energy Single-web has the same functions as Energy Twin-web except that it has only one webbing and one hook instead of two. Energy Single-web is manufactured as a tube with internal core. At the beginning of the webbing there is an external absorber mounted which is released in case of a fall and catches you. Tested and approved for users up to 100 kg. The cover on the absorber can easily be replaced if it becomes dirty or damaged to ensure that the rope underneath is protected in the best way. the bag make it easy to carry out an annual inspection according to EN 365. The lanyard is delivered without hooks.

Product properties

Brand	Cresto
Attaching connector 1	No Carabiner
Attaching connector 2	No Hook
Minimum breaking strength - MBS (kN)	15
Energy absorber	Yes
Fall indicator	Yes
Maximum load (kg)	100
Min/Max load (kg)	40/100
Maximum number of users	1
Mechanics	Tear-webbing absorber
Maximum working temperature (c)	100
Minimum working temperature (c)	-40

PPE-category	Category 3
Declaration of Conformity	Yes
EN-standard	EN 355 : 2002
Warranty	2+1 year when registered in Inspector
Identification	Serial number
Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
RFID	No

Article information

Article number	Article name	Colors	Net weight (kg)
012203754	Core, Single-Web	Black	0.4

Article number	Article name	GTIN	Tariff number	UNSPSC Code	Country of origin
012203754	Core, Single-Web	7350015791220	56090000	46182302	Slovakia