

# Cresto, Fusion Pro Twin-Flex 1602

## Fall Arrest Lanyard 1602

- CE and ANSI certified
- Approved for 140 kg
- Elastic webbing

EN 355 : 2002



### Product description

A double fall arrest lanyard is designed to suit you who need to move when you work at heights. With double hooks you always have a hook anchored when you move with the other hook. This is to provide the optimum security on, for example, scaffolding, mobile platforms or industries. Fusion Twin-Flex is manufactured as a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length of 1.8 meters. At the beginning of the rope there is an external absorber mounted which is released in case of a fall. Unlike Energy Twin-Flex this fall arrest lanyard is ANSI certified and are approved for a user weight up to 140 kg. Between the absorber and the lanyard there is an aluminum ring to increase flexibility in use

### Product properties

|                                      |  |
|--------------------------------------|--|
| Brand                                | Cresto   |
| Attaching connector 1                | ANSI and CE certified triple lock carabiner in aluminum    |
| Attaching connector 2                | Big ANSI and CE certified aluminum hook with 64 mm opening |
| Minimum breaking strength - MBS (kN) | 25   |
| Energy absorber                      | Yes  |
| Fall indicator                       | Yes  |
| Gate strength (kN)                   | 16   |
| Material                             | Polyamide, Polyester                                       |
| Maximum load (kg)                    | 140  |
| Maximum number of users              | 1  |
| Mechanics                            | Tear-webbing absorber                                      |
| Maximum working temperature (c)      | 100  |

|                                 |  |
|---------------------------------|--|
| Minimum working temperature (c) | -40  |
| Declaration of Conformity       | Yes  |
| EN-standard                     | EN 355 : 2002  |
| Warranty                        | 2+1 year when registered in Inspector  |
| Identification                  | Serial number  |
| Annual inspection               | Yes, every 12 months   |
| Life span                       | 10 + 2 years. Product lifecycle 10 years + 2 years stock keeping             |
| Notified body                   | 1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic |
| Other standards                 | ANSI Z359.13   |
| RFID                            | Yes  |

Article information

| Article number | Article name                          | Colors | Net weight (kg) |
|----------------|---------------------------------------|--------|-----------------|
| 012203835      | Fusion Pro Twin-Flex, 1,8m            | Black  | 2.09            |
| 012203836      | Fusion Pro Twin-Flex, 1,8m Black hook | Black  | 2.09            |

| Article number | Article name                          | GTIN          | Tariff number | UNSPSC Code | Country of origin |
|----------------|---------------------------------------|---------------|---------------|-------------|-------------------|
| 012203835      | Fusion Pro Twin-Flex, 1,8m            | 7350015799967 | 56090000      | 46182302    | Slovakia          |
| 012203836      | Fusion Pro Twin-Flex, 1,8m Black hook | 7350015791923 | 56090000      | 46182302    | Slovakia          |

| Article number | Article name                          | Packaging type | W(cm) | H(cm) | L(cm) | Gross weight (kg) | Pieces / Pack |
|----------------|---------------------------------------|----------------|-------|-------|-------|-------------------|---------------|
| 012203835      | Fusion Pro Twin-Flex, 1,8m            | Carton         | 0     | 0     | 0     | 2.1               | 1             |
| 012203836      | Fusion Pro Twin-Flex, 1,8m Black hook |                |       |       |       | 2.1               | 1             |