

Cresto, Core Twin-Flex H 1508

Fall arrest lanyard 1508

- Twin fall arrest lanyard
- 60 mm hooks
- 30 mm flexible webbing



EN 355 : 2002

Product description

A double fall arrest lanyard is designed to suit you who need to move when you work at heights. With double hooks, you always have a hook anchored when you move with the other hook. This is to provide the optimal security on, for example, scaffolding, mobile platforms or industries. Core Twin-Flex is manufactured as a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length. At the beginning of the rope, there is an external absorber mounted which is released in case of a fall and catches you. Tested and approved for users up to 100 kg. The cover on the absorber can easily be replaced if it becomes dirty or damaged to ensure that the rope underneath is protected in the best way.

Product properties

Brand	Cresto
Attaching connector 1	Oval screwgate steel carabiner
Attaching connector 2	Big hook with 60 mm opening
Minimum breaking strength - MBS (kN)	15
Energy absorber	Yes
Fall indicator	Yes
Maximum load (kg)	100
Min/Max load (kg)	40/100
Maximum number of users	1
Mechanics	Tear-webbing absorber
Maximum working temperature (c)	100
Minimum working temperature (c)	-40

PPE-category	Category 3
Declaration of Conformity	Yes
EN-standard	EN 355 : 2002
Warranty	2+1 year when registered in Inspector
Identification	Serial number
Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Notified body	1019, VVUU, a.s., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
RFID	No

Article information

Article number	Article name	Colors	Net weight (kg)
012203782	Cresto, Core Twin-Flex H, 1,9m	Yellow	1.495

Article number	Article name	GTIN	Tariff number	UNSPSC Code	Country of origin
012203782	Cresto, Core Twin-Flex H, 1,9m	7350015791268	56090000	46182302	Slovakia

Article number	Article name	Packaging type	Pieces / Pack
012203782	Cresto, Core Twin-Flex H, 1,9m	Carton	1