

RED PRO X EXTENDED

Rescue and evacuation device, box

- · Extremely good lifting capacity
- Water sealed brake housing
- · Intuitive and easy to use

Standards:

EN 341: 2011

EN 1496 : 2017

ANSI Z359.4-2013

CSA Z259.2.3-12



Product description

The latest generation automatic evacuation and rescue device with superior properties.

RESQ RPX is the latest generation of rescue and evacuation equipment from RESQ – designed and developed for easy use with intuitive functions. The RPX can handle most rescue scenarios in various industries and extreme environments, from evacuation from high heights, lifting from deep shafts to advanced rescues, the height worker can feel confident that the equipment performance is verified.

The design and functionality of the device are based on insights from professionals working at heights daily. RPX is designed to give height workers verified confidence in extreme environments and for easy implementation of user-training and inspections.

Single-sided use for safe handling - all features on frontside - no more losing valuable time, twisting and turning the device to double-check. Universal power tool-interface for heavy lifting, up to 255m. Top-mounted swivel for optimal positioning, even in tight conditions and confined space. Laser printed, easy to read data and pictograms, engraved direct and permanently on the body. 280 kg – 255m verified and tested decent weight and height!

The device comes with a lifting function where the connection of machine-driven accessories simplifies and facilitates lifting at longer distances as standard. With the help of a power tool, the equipment can lift a load of 140 kg at a distance of 255 meters.

RPX requires a minimum of training which equals Low TCO for maintenance of training certificates for your workforce. Due to the easily recognizable and intuitive design on both rescue equipment and accessories, the kit is both practical and cost-efficient to introduce to an already trained workforce which holds GWO or similar height training certificate.

RPX Extended is delivered as a complete set in RESQ Vacuum+ (service interval of 15 years), storage box in plastic and accessory kit.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

Product properties	
ProductMinMaxStorageTemperature:	-40/+60 °C
Brand:	RESQ
Material:	Polyamide, Aluminum , Techno polymers
Min/Max load (kg):	40/280
Minimum load (kg):	40
Maximum load (kg):	200
Maximum number of users:	2

Min/Max working	temperature (c):	-40/+60 °C						
EN-standard:		EN 341 : 2011, EN 1496 : 2017						
Other standards:		ANSI Z359.4-2013, CSA Z259.	ANSI Z359.4-2013, CSA Z259.2.3-12					
Notified body:		0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brondby, Denmark						
Annual inspection	:	Yes, every 12 months						
Life span:		15 + 15 years. Product lifecycle 15 years + 15 after service						
RFID:		Yes						
Warranty:		2 year						
Declaration of Cor	nformity:	Yes						
Rope:		Polyamide/polyamide 32-braided kernmantel construction 9,6mm						
Maximum rope ler	ngth (m):	255						
Fall indicator:		No						
Maximum descen	t:	255m						
Descent speed (m/s): 0,9-1,6								
Minimum breaking strength - MBS (kN):		20						
Energy absorber:		No						
Gate feature:		twist lock						
Gate strength (kN): 16								
Attaching connector 1: Device: Aluminum carabiner with swivel								
Attaching connect	or 2:	Rope: Aluminum carabiner						
Functions:		Descend function, Lifting function						
Extra functions:		Lift with external power source						
Mechanics:		Centrifugal brake						
Lifting mechanics:		Gear, ratio 1:9						
Adjustable under load:		Yes						
Reference	Article name		Size (m)	Colors	GTIN	Country of origin		
087003312050	RESQ, RPX200 Extended,	50m, box, Vacuum+, accs.	50	BLACK	7350015799080	Slovakia		
087003312075	RESQ, RPX200 Extended,	75m, box, Vacuum+, accs.	75	BLACK	7350015799097	Slovakia		
087003312083	RESQ, RPX200 Extended,	83m, box, Vacuum+, accs.	83	BLACK	7350015799462	Slovakia		

087003312090	RESQ, RPX200 Extended, 90m, box, Vacuum+, accs.	90	BLACK	7350015799479	Slovakia
087003312100	RESQ, RPX200 Extended, 100m, box, Vacuum+, accs.	100	BLACK	7350015799103	Slovakia
087003312105	RESQ, RPX200 Extended, 105m, box, Vacuum+, accs.	105	BLACK	7350015799486	Slovakia
087003312125	RESQ, RPX200 Extended, 125m, box, Vacuum+, accs.	125	BLACK	7350015799110	Slovakia
087003312140	RESQ, RPX200 Extended, 140m, box, Vacuum+, accs.	140	BLACK	7350015799493	Slovakia
087003312150	RESQ, RPX200 Extended, 150m, box, Vacuum+, accs.	150	BLACK	7350015799127	Slovakia
087003323160	RESQ, RPX200 Extended, 160m, box, Vacuum+, accs.	160	BLACK	7350015799509	Slovakia
087003323175	RESQ, RPX200 Extended, 175m, box, Vacuum+, accs.	175	BLACK	7350015799134	Slovakia
087003323180	RESQ, RPX200 Extended, 180m, box, Vacuum+, accs.	180	BLACK	7350015799516	Slovakia
087003323200	RESQ, RPX200 Extended, 200m, box, Vacuum+, accs.	200	BLACK	7350015799141	Slovakia