

CRESTO, SIMO PRO H-A 2353

Work Positioning Lanyard 2353

- ANSI certified
- · Strong against sharpe edges
- · Certified as anchorpoint

Standards:

EN795B

EN358

ANSI Z359.3:2017



Product description

A work positioning lanyard with a simple one-hand adjustment and ANSI certified with ANSI carabiner and hook. End-loop for shortening the slack when climbing.

Simo Pro H-A is a work positioning lanyard of a strong and soft polyamide rope of the highest quality. With its smooth rope grab you can easily adjust the tension in the rope with one hand. This lanyard is tested and approved for users up to 140 kg and is unique thanks to its certification for many environments. A unique feature is that the lanyard can be used as an anchor point for, for example, rescue equipment.

This model has ANSI certified carabiner and a big ANSI certified hook with 64 mm opening.

| Product properties | |
|----------------------------------|--|
| Brand: | Cresto |
| Material: | Polyamide |
| Maximum load (kg): | 140 |
| Maximum number of users: | 1 |
| Minimum working temperature (c): | -40 |
| Maximum working temperature (c): | 100 |
| EN-standard: | EN795B, EN358, ANSI Z359.3:2017 |
| Notified body: | 1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic |
| Annual inspection: | Yes, every 12 months |
| Life span: | 10 + 2 years. Product lifecycle 10 years + 2 years stock keeping |
| RFID: | Yes |
| Warranty: | 2+1 year when registered in Inspector |
| Declaration of Conformity: | Yes |
| Rope: | 16 mm kern mantle rope in polyamide . |
| Fall indicator: | No |
| | |

| Minimum breaking | strength - MBS (kN): | 28 | | | | | |
|------------------------|---------------------------|---|----------|--------|---------------|-------------------|--|
| Energy absorber: | | No | | | | | |
| Gate opening (mm): | | 62 | | | | | |
| Gate strength (kN): | | 22 | | | | | |
| Attaching connector 1: | | ANSI certified trippellock carabiner in aluminum | | | | | |
| Attaching connector 2: | | Big ANSI certified aluminum hook with 64 mm opening | | | | | |
| Functions: | | Support function | | | | | |
| Mechanics: | | Spring-loaded lever locking. | | | | | |
| Adjustable under load: | | Yes | | | | | |
| Reference | Article name | | Size (m) | Colors | GTIN | Country of origin | |
| 012204065 | Cresto, Simo Pro H-A 1,0m | | 1 | BLACK | 7350015790346 | Slovakia | |
| 012204066 | Cresto, Simo Pro H-A 1,5m | | 1.5 | BLACK | 7350015790353 | Slovakia | |

| Reference | Article name | Size (m) | Colors | GTIN | Country of origin |
|-----------|---------------------------|----------|--------|---------------|-------------------|
| 012204065 | Cresto, Simo Pro H-A 1,0m | 1 | BLACK | 7350015790346 | Slovakia |
| 012204066 | Cresto, Simo Pro H-A 1,5m | 1.5 | BLACK | 7350015790353 | Slovakia |
| 012204067 | Cresto, Simo Pro H-A 1,8m | 1.8 | BLACK | 7350015790360 | Slovakia |
| 012204068 | Cresto, Simo Pro H-A 2,0m | 2 | BLACK | 7350015790377 | Slovakia |
| 012204069 | Cresto, Simo Pro H-A 2,5m | 2.5 | BLACK | 7350015790384 | Slovakia |