

# SN20 Y-SLING

## SN20 Y-Sling

- Dual-arm lanyard design for continuous safety while passing anchor points.
- Made from durable polyamide webbing, 20 mm wide, with a load capacity of at least 22 kN.
- Conforms to EN795, EN 566, and EN 354, ensuring top safety and quality standards.

Standards: **EN 354 : 2010** **EN 566 : 2017** **EN 795 : 2012 Type B**



### Product description

Elevate your safety gear with the SN20 Y Anchor Sling - your reliable partner in heights safety, designed for seamless movement through anchor points.

The SN20 Y Anchor Sling, crafted from high-strength polyamide webbing at a width of 20 mm, is designed for versatility and maximum safety. With a breaking strength of 22 kN and intended for use on a horizontal safety system, it allows for easier and safer passing of progressive anchor points. Thanks to its dual-arm design, users are secured even when navigating through anchor points. Meeting EN795, EN 566, and EN 354 standards, this sling is the professional's choice for secure anchorage.

### Product properties

Brand:	Cresto
Material:	Polyester
Maximum number of users:	1
Minimum working temperature (c):	-20
Maximum working temperature (c):	60
EN-standard:	EN 354 : 2010, EN 566 : 2017, EN 795 : 2012 Type B
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Annual inspection:	Yes, every 12 months
Life span:	10 years
RFID:	No
Warranty:	2 year
Declaration of Conformity:	Yes
Minimum breaking strength - MBS (kN):	30

Reference	Article name	Size (m)	Colors	GTIN	Country of origin
SSN20YR-070	SN20 Y sling 2 x 70 cm	0.7	RED	8588007909721	Slovakia

SSN20YR-080	SN20 Y sling 2 x 80 cm	0.8	RED	8588007909738	Slovakia
SSN20YR-090	SN20 Y sling 2 x 90 cm	0.9	RED	8588007909745	Slovakia
SSN20YR-120	SN20 Y sling 2 x 120 cm	1.2	RED	8588007909752	Slovakia