

SN20 Y-SLING

SN20 Y-Sling

- Dual-arm lanyard design for continuous safety while passing anchor points.
- Made from durable polyamide webbing, 20 mm wide, with a load capacity of at least 22 kN.
- Conforms to EN795, EN 566, and EN 354, ensuring top safety and quality standards.

Standards: **EN 354 : 2010** **EN 566 : 2017** **EN 795 : 2012 Type B**



Product description

Elevate your safety gear with the SN20 Y Anchor Sling - your reliable partner in heights safety, designed for seamless movement through anchor points.

The SN20 Y Anchor Sling, crafted from high-strength polyamide webbing at a width of 20 mm, is designed for versatility and maximum safety. With a breaking strength of 22 kN and intended for use on a horizontal safety system, it allows for easier and safer passing of progressive anchor points. Thanks to its dual-arm design, users are secured even when navigating through anchor points. Meeting EN795, EN 566, and EN 354 standards, this sling is the professional's choice for secure anchorage.

Product properties

Brand:	Cresto
Material:	Polyester
Maximum number of users:	1
Minimum working temperature (c):	-20
Maximum working temperature (c):	60
EN-standard:	EN 354 : 2010, EN 566 : 2017, EN 795 : 2012 Type B
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Annual inspection:	Yes, every 12 months
Life span:	10 years
RFID:	No
Warranty:	2 year
Declaration of Conformity:	Yes
Minimum breaking strength - MBS (kN):	30

Reference	Article name	Size (m)	Colors	GTIN	Country of origin
SSN20YR-070	SN20 Y sling 2 x 70 cm	0.7	RED	8588007909721	Slovakia

SSN20YR-080	SN20 Y sling 2 x 80 cm	0.8	RED	8588007909738	Slovakia
SSN20YR-090	SN20 Y sling 2 x 90 cm	0.9	RED	8588007909745	Slovakia
SSN20YR-120	SN20 Y sling 2 x 120 cm	1.2	RED	8588007909752	Slovakia