

RESQ SOLO X WIND

Evacuation device IQDX

- Pre-configured additional friction
- Automated, intuitive design for effortless emergency descents
- Certified for use in extreme temperatures from -40°C to +60°C

Standards: **EN 341 : 2011** **ANSI Z359.4-2013**



Product description

A compact, fully automatic evacuation device engineered for quick, safe descents from heights up to 300 meters. Light as a smartphone, yet powerful enough to save lives when seconds matter.

RESQ Solo X is the world's smallest and lightest personal evacuation device, designed for ultimate simplicity and reliability in emergency situations. It features a fully automated braking system, allowing for controlled descents at 1.4 m/sec. With minimal setup — connect and go — Solo X is ready to perform when you need it most. Its compact design, weighing just 5.15 kg for a 100-meter kit, ensures it won't weigh you down, making it ideal for high-risk work environments. Certified for use in extreme temperatures, it's built to last with minimal upkeep, offering a lifespan of up to 30 years.

Product properties

ProductIncludedProducts: RESQ, Aramid sling, Covered, 7mm, 1m EN/ANSI

ProductMinMaxStorageTemperature: -40/+60 °C

Brand: RESQ

Material: Aluminum , Steel, Aramid

Min/Max load (kg): 30/141

Maximum number of users: 1

Min/Max working temperature (c): -40/+60 °C

EN-standard: EN 341 : 2011

Other standards: ANSI Z359.4-2013

Notified body: 0511, AUVA, Allgemeine Unfallversicherungsanstalt Sicherheitstechnische Prüfstelle - Wienerbergstrasse 11 1100 Wien, Austria

Annual inspection: Yes, every 12 months

Life span: 15 + 15 years. Product lifecycle 15 years + 15 after service

RFID: Yes

Warranty: 2 year

Declaration of Conformity:	Yes
Rope:	4,8mm TWARON Aramide hollow core braided rope
Maximum rope length (m):	300
Maximum descent:	1 x 300m
Descent speed (m/s):	0,5-2
Minimum breaking strength - MBS (kN):	14
Gate feature:	Twist lock
Gate opening (mm):	17
Gate strength (kN):	16
Attaching connector 1:	Steel carabiner
Functions:	Descend function
Extra functions:	Mesh bag for rope connected directly in SOLO X device carabiner
Mechanics:	Centrifugal brake system
Adjustable under load:	Yes

Reference	Article name	Size (m)	Colors	GTIN	Country of origin
08110222100	RESQ SOLO X Wind 100m	100	BLACK	7350015792241	Slovakia
08110222125	RESQ SOLO X Wind 125m	125	BLACK	7350015792289	Slovakia
08110222150	RESQ SOLO X Wind 150m	150	BLACK	7350015792296	Slovakia
08110222175	RESQ SOLO X Wind 175m	175	BLACK	7350015792302	Slovakia
08110222200	RESQ SOLO X Wind 200m	200	BLACK	7350015792371	Slovakia
08110223225	RESQ SOLO X Wind 225m	225	BLACK	7350015792401	Slovakia
08110223250	RESQ SOLO X Wind 250m	250	BLACK	7350015792449	Slovakia
08110223275	RESQ SOLO X Wind 275m	275	BLACK	7350015792463	Slovakia
08110223300	RESQ SOLO X Wind 300m	300	BLACK	7350015792470	Slovakia
08110222050	RESQ SOLO X Wind 50m	50	BLACK	7350015792227	Slovakia
08110222075	RESQ SOLO X Wind 75m	75	BLACK	7350015792234	Slovakia