

CRESTO, CORE ADJUSTABLE 1235

Fall arrest line 1235

- Durable 11,5 mm polyamide rope
- For users up to 140 kg
- Edge tested

Standards: **EN 353-2 : 2002** **PPE-R/11.075,V1**



Product description

Cresto Core fall arrest line with an adjustable rope grab tested and approved for users up to 140 kg. And approved with fall over edge.

This fall arrest line is made of a 11,5 mm thick rope of high quality, and the adjustable rope grab allows the product to be used easily in, for example, roof work.

The fall arrest line is tested and approved for users up to 140 kg. And approved with fall over edge.

The textile fall arrester is located in an openable bag to make it easier to carry out an annual inspection according to EN 365.

Product properties

Brand:	Cresto
Material:	Polyamide
Maximum load (kg):	140
Maximum number of users:	1
Minimum working temperature (c):	-40
Maximum working temperature (c):	100
EN-standard:	EN 353-2 : 2002
Other standards:	PPE-R/11.075,V1
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Annual inspection:	Yes, every 12 months
Life span:	10 years
RFID:	Yes
Warranty:	2+1 year when registered in Inspector
Declaration of Conformity:	Yes
Rope:	11,5 mm kern mantle rope in polyamide from Lanex
Minimum breaking strength - MBS (kN):	15

Energy absorber:	Yes
Attaching connector 1:	Oval screwgate carabiner in steel,
Attaching connector 2:	Oval screwgate carabiner in steel,
Mechanics:	Tear-webbing absorber on the rope grab
Adjustable under load:	No

Reference	Article name	Size (m)	Colors	GTIN	Country of origin
012202910	Cresto, Core Adjustable, 10 m	10	BLACK/GREY	7350015791572	Slovakia
012202915	Cresto, Core Adjustable, 15 m	15	BLACK/GREY	7350015791596	Slovakia
012202905	Cresto, Core Adjustable, 5 m	5	BLACK/GREY	7350015791589	Slovakia