

CRESTO, SINGLE-EDGE H 1503

Fall arrest lanyard 1503

- Single fall arrest lanyard
- 60 mm hooks
- Edge tested 11,5 mm polyamide rope



Standards: **EN 355 : 2002** **PPE-R/11.074, V3**

Product description

A single fall arrest lanyard with rope and one hook.

A fall arrest lanyard with rope that is tested and approved for users up to 100 kg. The 12 mm thick rope makes it enduring. The fall arrester is located in an openable bag to make it easier to carry out an annual inspection in accordance with EN 365. The product is suitable for work where the user does not need to reconnect. Tested and approved with fall over edge.

Product properties

Brand:	Cresto
Min/Max load (kg):	40/100
Maximum load (kg):	100
Maximum number of users:	1
Minimum working temperature (c):	-40
Maximum working temperature (c):	100
EN-standard:	EN 355 : 2002, PPE-R/11.074, V3
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Annual inspection:	Yes, every 12 months
Life span:	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
RFID:	Yes
Warranty:	2+1 year when registered in Inspector
Declaration of Conformity:	Yes
Fall indicator:	Yes
Minimum breaking strength - MBS (kN):	15
Energy absorber:	Yes

Attaching connector 1:		No Carabiner			
Attaching connector 2:		No Hook			
Mechanics:		Tear-webbing absorber			
Reference	Article name	Size (m)	Colors	GTIN	Country of origin
012203732	Cresto, Single-Edge, (No hooks)	2	BLACK/GREY	7350015791176	Slovakia
012203730	Cresto, Single-Edge H	2	BLACK/GREY	7350015791169	Slovakia