

WIRE ANCHOR STROP

Anchoring 9103

- 6 mm wire
- For around or straight use
- Breaking strength 25 kN

Standards: **EN 795 : 2012** **TS 16415:2013**



Product description

Strong wire sling that is used as a temporary anchor point. Complement the sling with carabiner 012250064 CT, Pillar Steel SG.

WS is a 6 mm thick wire sling with galvanized wire, plastic cover and aluminum pressed ferrules.

Product properties

Brand:	ISC
Material:	Galvanized steel
Maximum load (kg):	240
Maximum number of users:	2
Minimum working temperature (c):	-40
Maximum working temperature (c):	100
EN-standard:	EN 795 : 2012
Other standards:	TS 16415:2013
Notified body:	0102, SGS UK Ltd, Unit 202b Worle Parkway, Weston-superMare, Somerset BS22 6WA, United Kingdom
Annual inspection:	Yes, every 12 months
RFID:	No
Warranty:	2+1 year when registered in Inspector
Declaration of Conformity:	Yes
Rope:	6 mm galvanized wire
Minimum breaking strength - MBS (kN):	25

Reference	Article name	Size (m)	Colors	GTIN	Country of origin
-----------	--------------	----------	--------	------	-------------------

012255105	ISC, Wire Anchor Strop, 6mm, 1m, plastic cover	1	GREY	5060508269540	United Kingdom
-----------	--	---	------	---------------	----------------