ACRESTO SAFETY

CRESTO, WORKER PRO+ 1124

Harness 1124

- · Patented attachment webbing loops in front
- · Designed to fit women as well
- Ergonomic support belt for positioning

Standards:

EN 358 : 2018

EN 361: 2002



Product description

A patented fall protection harness developed for a broad spectrum of fall protection requirements. The focus of the harness design is on ergonomics and comfort. It's flexible and has great adjustment possibilities, thus it enables both women and men to achieve a customized fit.

The design of the harness and the adjustable shoulder straps provide optimal user fitting in terms of size and comfort. Making the harness "one-size", it enables users from approximately 165 cm to 195 cm in height to fit the harness guite nicely.

The patented attachment webbing loops are located at waist height to keep the lanyard/rope out of the way as much as possible, and to give the user a free field of operation, as well as not putting pressure against the chest while working and climbing.

In the event of a fall the loops move up to the chest providing a high attachment point, positioning the body correctly in a fall. Same basis design as harness 1123, equipped with a support belt.

Harriess 1120, equipped with a support belt.				
Product properties				
Brand:	Cresto			
Material:	Polyester Nordguard ™			
Min/Max load (kg):	30 / 140			
Maximum load (kg):	140			
Maximum number of users:	1			
Min/Max working temperature (c):	- 40 / 100			
Minimum working temperature (c):	-40			
Maximum working temperature (c):	100			
EN-standard:	EN 358 : 2018, EN 361 : 2002			
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic			
Annual inspection:	Yes, every 12 months			
Life span:	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping			
RFID:	Yes			
Warranty:	2+1 year when registered in Inspector			

Declaration of Conformity:	Yes
Chest buckles:	Quick buckles in steel with stainless components Strength >20kN
Leg buckles:	Quick buckles in steel with stainless components Strength >20kN
Front A-point:	Textile sliding angled loop >15kN. Not for static work.
Back A-point:	Galvanized steel 45 mm> 30kN
Side D-rings:	Galvanized steel 45 mm> 30kN
Adjustable under load:	No
Padding material:	Breathable 3-D mesh

Reference	Article name	Size	Colors	GTIN	Country of origin
012200143	Cresto, Worker Pro+, one size	os	BLACK/GREY	7350015794351	Slovakia