

# CRESTO, WORKER ADJUSTABLE 1215

## Fall arrest line 1215

- Durable 12 mm polyamide rope
- For users up to 140 kg
- Easily adjustable rope grab

Standards: **EN 353-2 : 2002**



## Product description

A fall arrest line with an adjustable rope grab tested and approved for users up to 140 kg.

This fall arrest line is made of a 12 mm thick rope of high quality, and the adjustable rope grab allows the product to be used easily in, for example, roof work. The fall arrest line is tested and approved for users up to 140 kg. The textile fall arrester is located in an openable bag to make it easier to carry out an annual inspection according to EN 365.

## Product properties

Brand:	Cresto
Material:	Polyamide
Maximum load (kg):	140
Maximum number of users:	1
Minimum working temperature (c):	-40
Maximum working temperature (c):	100
EN-standard:	EN 353-2 : 2002
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Annual inspection:	Yes, every 12 months
Life span:	10 years
RFID:	Yes
Warranty:	2+1 year when registered in Inspector
Declaration of Conformity:	Yes
Rope:	12 mm kern mantle rope in polyamide by the brand Patron from Teufelberger
Minimum breaking strength - MBS (kN):	15
Energy absorber:	Yes

Attaching connector 1:		Oval twist carabiner in aluminum, mounted with captive pin			
Attaching connector 2:		Oval twist carabiner in aluminum, mounted with captive pin			
Mechanics:		Tear-webbing absorber on the rope grab			
Adjustable under load:		No			
Reference	Article name	Size (m)	Colors	GTIN	Country of origin
012202705	Cresto, Worker Adjustable, 5 m	5	RED	7350015798588	Slovakia
012202710	Cresto, Worker Adjustable, 10 m	10	RED	7350015798052	Slovakia
012202715	Cresto, Worker Adjustable, 15 m	15	RED	7350015798069	Slovakia