

# SMARTLINE X ULTRA VACUUM

## Evacuation Device

- Extended lifetime
- Capacity
- Lightweight

Standards: **EN 341 : 2011**



## Product description

Smartline X is one of the worlds smallest evacuation device on the market with a remarkable capacity of 140 kg user weight and 200 meter descent distance. This device is delivered in vacuum sealed packaging with RESQ Quick Access opening.

RESQ Smartline X is in its class the smallest and lightest personal evacuation equipment to its high capacity and size. With a maximum load of 140 kg, maximum descent distance of 200 meters and a total weight of 3.8 kg (200 m), Smartline X becomes unique.

With weights from 2 to 3,8 kg, it's easy to carry the equipment attached to the harness to ensure availability in an emergency, wherever you are in the elevated workplace.

The Aramid rope has an incredible strength to diameter ratio and has heat resistance over 480 C. Smartline X can even be suitable where the sudden fire appears.

We have combined two fantastic solutions into one, the original patented vacuum pack and Smartline X, both with great track records and combined them into one. The vacuum pack has been customized to fit the Smartline X. The result is a smaller and softer pack which can be opened by tearing along the opening seam. We call it RESQ Quick Access.

By packing the equipment in vacuum, moisture cannot be present in the package. It's also impossible for the rope and other components to be worn or rubbed against each other. With Smartline X vacuum you only need to inspect the vacuum pack once a year, this enables us to prolong the total lifespan of the product to 10 years, as long as the Smartline X Vacuum pack remains intact.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

## Product properties

Brand: RESQ

Material: Aluminum , Nylon, Aramid

Minimum load (kg): 60

Maximum load (kg): 140

Maximum number of users: 1

Minimum working temperature (c): -40

Maximum working temperature (c): 50

EN-standard: EN 341 : 2011

Notified body: 0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brøndby, Denmark

Annual inspection:	Yes, every 12 months
Life span:	10 years
RFID:	Yes
Warranty:	2 year
Declaration of Conformity:	Yes
Rope:	Aramid 5,5mm, 16 twill braid coreless construction
Maximum rope length (m):	200
Maximum descent:	200 meter
Descent speed (m/s):	0,5-2m/s
Energy absorber:	Yes
Gate opening (mm):	20
Attaching connector 1:	Device: Aluminum carabiner tri-lock
Attaching connector 2:	Rope/absorber: Aluminum carabiner tri-lock
Functions:	Descend function
Mechanics:	Friction brake
Lifting mechanics:	Method 1:3
Adjustable under load:	Yes

Reference	Article name	Size (m)	Colors	GTIN	Country of origin
012230130	RESQ, Smartline X Ultra Vacuum, 50m	50	RED	7350015798045	Slovakia
012230131	RESQ, Smartline X Ultra Vacuum, 75m	75	RED	7350015798199	Slovakia
012230137	RESQ, Smartline X Ultra Vakuum, 80m	80	RED	7350015799813	Slovakia
012230132	RESQ, Smartline X Ultra Vacuum, 100m	100	RED	7350015798205	Slovakia
012230133	RESQ, Smartline X Ultra Vacuum, 125m	125	RED	7350015798212	Slovakia
012230134	RESQ, Smartline X Ultra Vacuum, 150m	150	RED	7350015798229	Slovakia
012230136	RESQ, Smartline X Ultra Vacuum, 160m	160	RED	7350015799592	Slovakia
012230135	RESQ, Smartline X Ultra Vacuum, 200m	200	RED	7350015798236	Slovakia