

RED PRO X ORIGINAL

Rescue and evacuation device, box

- Extremely good lifting capacity
- Water sealed brake housing
- Intuitive and easy to use

Standards: **EN 341 : 2011** **EN 1496 : 2017** **ANSI Z359.4-2013**

CSA Z259.2.3-12



Product description

The latest generation automatic evacuation and rescue device with superior properties.

RESQ RPX is the latest generation of rescue and evacuation equipment from RESQ – designed and developed for easy use with intuitive functions. The RPX can handle most rescue scenarios in various industries and extreme environments, from evacuation from high heights, lifting from deep shafts to advanced rescues, the height worker can feel confident that the equipment performance is verified.

The design and functionality of the device are based on insights from professionals working at heights daily. RPX is designed to give height workers verified confidence in extreme environments and for easy implementation of user-training and inspections.

Single-sided use for safe handling - all features on frontside - no more losing valuable time, twisting and turning the device to double-check. Universal power tool-interface for heavy lifting, up to 255m. Top-mounted swivel for optimal positioning, even in tight conditions and confined space. Laser printed, easy to read data and pictograms, engraved direct and permanently on the body. 280 kg – 255m verified and tested decent weight and height!

The device comes with a lifting function where the connection of machine-driven accessories simplifies and facilitates lifting at longer distances as standard. With the help of a power tool, the equipment can lift a load of 140 kg at a distance of 255 meters.

RPX requires a minimum of training which equals Low TCO for maintenance of training certificates for your workforce. Due to the easily recognizable and intuitive design on both rescue equipment and accessories, the kit is both practical and cost-efficient to introduce to already trained workforce which holds GWO or similar height training certificate.

RPX Original is delivered as a complete set in RESQ Vacuum (service interval of 10 years), storage box in plastic and accessory kit.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

Product properties

ProductMinMaxStorageTemperature: -40/+60 °C

Brand: RESQ

Material: Polyamide, Aluminum , Techno polymers

Min/Max load (kg): 40/280

Minimum load (kg): 40

Maximum load (kg): 200

Maximum number of users: 2

Min/Max working temperature (c):	-40/+60 °C				
EN-standard:	EN 341 : 2011, EN 1496 : 2017				
Other standards:	ANSI Z359.4-2013, CSA Z259.2.3-12				
Notified body:	0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brøndby, Denmark				
Annual inspection:	Yes, every 12 months				
Life span:	10 + 10 years. Product lifecycle 10 years + 10 years after service				
RFID:	Yes				
Warranty:	2 year				
Product Includes:	Backpack 9450,Rescue accessory kit,Sling 3683,Sling 3683,Rope grab for rescue,Edge Protection kit,Pulley,Carabiner N-267G-CP				
Declaration of Conformity:	Yes				
Rope:	Polyamide/polyamide 32-braided kermantel construction 9,6mm				
Maximum rope length (m):	255				
Fall indicator:	No				
Maximum descent:	255m				
Descent speed (m/s):	0,9-1,6				
Minimum breaking strength - MBS (kN):	20				
Energy absorber:	No				
Gate feature:	tri lock				
Gate strength (kN):	16				
Attaching connector 1:	Device: Aluminum carabiner with swivel				
Attaching connector 2:	Rope: Aluminum carabiner				
Functions:	Descend function, Lifting function				
Extra functions:	Lift with external power source				
Mechanics:	Centrifugal brake				
Lifting mechanics:	Gear, ratio 1:9				
Adjustable under load:	Yes				
Reference	Article name	Size (m)	Colors	GTIN	Country of origin
087003212050	RESQ, RPX200 Original, 50m, box, vacuum, accs.	50	BLACK	7350015799158	Slovakia

087003212075	RESQ, RPX200 Original, 75m, box, vacuum, accs.	75	BLACK	7350015799165	Slovakia
087003212083	RESQ, RPX200 Original, 83m, box, vacuum, accs.	83	BLACK	7350015799400	Slovakia
087003212090	RESQ, RPX200 Original, 90m, box, vacuum, accs.	90	BLACK	7350015799417	Slovakia
087003212100	RESQ, RPX200 Original, 100m, box, vacuum, accs.	100	BLACK	7350015799172	Slovakia
087003212105	RESQ, RPX200 Original, 105m, box, vacuum, accs.	105	BLACK	7350015799424	Slovakia
087003212125	RESQ, RPX200 Original, 125m, box, vacuum, accs.	125	BLACK	7350015799189	Slovakia
087003212140	RESQ, RPX200 Original, 140m, box, vacuum ,accs.	140	BLACK	7350015799431	Slovakia
087003212150	RESQ, RPX200 Original, 150m, box, vacuum, accs.	150	BLACK	7350015799196	Slovakia
087003213160	RESQ, RPX200 Original, 160m, box, vacuum, accs.	160	BLACK	7350015799448	Slovakia
087003223175	RESQ, RPX200 Original, 175m, box, vacuum, accs.	175	BLACK	7350015799202	Slovakia
087003223180	RESQ, RPX200 Original, 180m, box, vacuum, accs.	180	BLACK	7350015799455	Sweden
087003223200	RESQ, RPX200 Original, 200m, box, vacuum, accs.	200	BLACK	7350015799219	Slovakia